

PRODUCT DATASHEET

iID® Transponder

MINI-TAGspecial 4.5

HF-RFID miniature transponder, for extreme environmental conditions, mounting in metal

- passive RFID communication 13.56 MHz
- round TAG, diameter 4.5 (5.0) mm
- PEEK packaging
- for mounting in metal surface
- 64 kbit, 16 kbit or 1 kbit EEPROM memory
- designed for measuring tool management solutions, aircraft and automotive part tagging

These transponder device is an integral part of *microsensys* iID® system solution.

This TAG operates with *microsensys* standard RFID reader components and high sensitive demodulators.



microsensys GmbH
In der Hochstedter Ecke 2
D 99098 Erfurt

TEL +49-361-59874 0
E-MAIL info@microsensys.de
FAX +49-361-59874 17
WEB www.microsensys.de

microSensys
RFID in motion

This data sheet is subject to change
contact [microsensys](mailto:info@microsensys.de) for latest information

MINI-TAGsp45 003.docx

RFID Technology:	closed coupling RFID system iID®2000, ISO 15693 or proprietary	
Chip Type:	I-CODE®, iID®-G, iID®-K others on request	
Carrier Frequency:	13.56 MHz	
Communication Rate:		down link 26.4 kbps or 106 kbps
Communication Distance:	0 ... 3 mm	dependent on reader antenna, chip type and metal environment
Memory:	EEPROM	endurance >100.000 cycles, data retention > 10 years
Memory Capacity:		64 kbit, 16 kbit and 896 bit EEPROM available
Special Functionality:		see data sheet of chip manufacturer
Operating Temperature:	-25°C ... +65°C	
Storage Temperature:	-25°C ... 150°C	long term max. +85°C, short time 180°C
Dimensions:	D 4.5 +/-0.1 mm (outside of metal 5.0 mm), TH 2.0 mm	
Packaging Material:	PEEK, back side epoxy	inlet mixed ferrite epoxy
Mounting Instructions:	PEEK material in black or nature colour, depending on the availability using flat in metal possible plane side on top	
Marking:	no marking	recommended glue: 2K-EP "plus endfest 300" UHU GmbH Germany optional colour marking
Appropriate RFID Reader:	PEN reader POCKET reader K3 UNI13 or Q10	with RS232TTL, USB or Bluetooth interface, with USB and Bluetooth interface especially for mobile data capture read write module with K3, for <i>microsensys</i> OEM partner only
HOST Command Set:	see actual API documentation of <i>microsensys</i> iID® driver engine or data sheets of silicon chip manufacturer	
Software:	different software for Windows PC or mobile devices available, for application software please ask at info@microsensys.de	

Type :	10.26.515*	10.54.515	11.47.515	* on inquiry
Chip Type:	iID-K	iID-G	SLIX-S	
Standard:	ISO 14443B	ISO 15693-2	ISO 15693	
Memory:	64,000; EEPROM	16,000; EEPROM	1,300; EEPROM	bit
Communication Rate:	106	26.4	26.4	kbps
Communication Distance:	1.5	2	3	mm
				measured with PENmini